

A survey by D.B. Hasbrook on April23, 1851 indicates a stone set with the following witnesses: 28"red oak bearing south 55.5 degrees, thence west 74 links; and a 40" white oak bearing north 77.25 degrees, thence west 157 links. (Franklin Legal Book p. 27) Corner referenced by G.W.S. on 10/10/63 and called an iron pin over stone. Corner referenced by Mcland on 3/26/69 and called an iron pin over stone. Corner referenced by Mcland on 5/1/72 and called an iron pin over stone down 6". Corner referenced by Wilcoxen on 7/21/75 and called a rebar. Corner referenced by Wilcoxen on 8/17/79 and called a rebar. Corner referenced by Wilcoxen on 8/17/79 and called a rebar. Corner referenced by Wilcoxen on 9/28/94 and called a p.k. Nail over stone. Corner referenced by Kiste on 8/20/99 and called a p.k. Nail. Corner excavated by Wilcoxen on 10/23/02 and a p.k. Nail was found 3" down. A stone was found 10" down. A #205 cast iron Harrison Monument was

	14042305	
REF.	DISTANCE	DESCRIPTION
1.	82.85'	Mag nail w/brass washer E PwP#797 B 18"up
2.	133.80'	Mag nail w/bw W PwP#396-827 12"up
3.	33.53'	Cut 'x' S-end of concrete sidewalk
4.	115.52'	Mag nail w/brass washer E PwP#614-796 24"up